



---

## KIT PART NUMBER 6408029

### INSTRUCTIONS FOR REPLACING AN EVERPURE WATER FILTER WITH A HYDROLIFE WATER FILTER

---

CHECK THE PARTS RECEIVED IN THE KIT WITH THE PARTS LIST IN THESE INSTRUCTIONS. IF ANY PARTS ARE MISSING, CONTACT THE NATIONAL VENDORS PARTS DEPARTMENT IMMEDIATELY.

---

Read these instructions carefully before installing the kit.  
Keep these instructions for part numbers and for future reference.

#### This kit contains the following:

INDEX	PART NUMBER	DESCRIPTION	QUANTITY
1	6338027	HEAD - BRACKET - HYDRO LIFE	1
2	6330035	INSTALLATION INSTRUCTIONS - HYDRO LIFE FILTER	1
3	6408028	HOUSING - CARTRIDGE - "O" RING - HLV192H	1

Proceed as follows:

#### WARNING

Lethal voltages exist inside this machine, particularly when working with wet parts. Be sure the main power switch is OFF and the machine is unplugged prior to starting work.

1. Remove electrical power from the machine.
2. Turn off water to the machine.
3. Remove the existing water filter.
4. Remove the inlet water line from the existing filter head.
5. Remove the outlet water line from the existing filter head.
6. Remove the existing filter head and bracket.
7. Assemble the new bracket and black housing cap. Orient the inlet and outlet posts the same way they were on the filter head you removed in step 6.
8. Install the new head and bracket assembly. Connect the inlet water line to the quick connect fitting with shut-off valve. Connect the outlet water line to the other quick connect fitting.
9. Push both fittings down onto the posts as far as possible. You should be able to push the fittings down over each post to within 1/8" or less above the end.
10. Remove the clear plastic wrap from the filter cartridge. Insert the end with the two "O" rings into the center collar on the underside of the black housing cap.



11. Make sure the "O" ring in the white sump is seated correctly in the groove below the threads. Slide the white sump up over the filter cartridge to the black cap. Screw the white sump to the black cap until the white sump is securely fastened.
12. Turn on the water to the machine. Turn water on at the on/off valve located on the inlet water line fitting. Carefully check for leaks.
13. Restore electrical power to your machine and return it to service.

