

---

**KIT PART NUMBERS 4850065, 6330065**  
**INSTRUCTIONS FOR REPLACING THE HOT WATER TANK SPRAY HOSE**  
**ASSEMBLY IN A REFRESHMENT CENTER OR HOT DRINK CENTER**  
**MACHINE**

**CHECK THE PARTS RECEIVED IN THE KIT WITH THE PARTS LIST IN THESE INSTRUCTIONS. IF ANY PARTS ARE MISSING, CONTACT THE NATIONAL VENDORS PARTS DEPARTMENT**

Read these instructions carefully before installing the kit.  
Keep these instructions for part numbers and for future reference.

**WARNING**

*Disconnect the power cord from the wall and drain all water from the hot water tank before attempting to install this kit. Failure to follow these instructions completely may result in serious injury.*

This kit contains the following :

<b>PART NUMBER</b>	<b>DESCRIPTION</b>	<b>QUANTITY</b>
<b>CONTENTS OF KIT NUMBER 4850065</b>		
6138265	HOSE - SPRAY	1
6158063	CLAMP - HOSE	1
6338059	FITTING - .125 NPT X .375 BARB	1
<b>CONTENTS OF KIT NUMBER 6330065</b>		
6338060	HOSE - SPRAY - 48 IN.	1
6158063	CLAMP - HOSE	1
6338059	FITTING - .125 NPT X .375 BARB	1

1. Remove the power cord from the wall outlet.
2. Turn off the water to the machine.
3. Locate the drain tube above the waste pail. Release the drain clamp on the tubing and allow the hot water to drain into the waste pail. Be careful not to overfill the waste pail. Allow the hot water tank to drain completely.
4. After the hot water tank has drained completely, raise the spray nozzle and tube above the bottom of the water tank. Squeeze the handle to allow the tube to drain completely. Failure to drain the tubing could result in burns when the hose is cut.
5. After all water is drained, use a utility knife cut the spray tubing 12 inches from the "Y" connector.
6. Place the new hose clamp, P/N 6158063, on the tubing and insert the barbed end of the fitting, P/N 6338059, into the tube, then tighten the clamp on the tube around the barbed fitting.

- 
7. Apply thread sealant to the threads on the end of the new spray nozzle hose, (6338050 for the Hot Drink Center) or (6138265 for the Refreshment Center 3).
  8. Tighten the spray nozzle hose into the brass fitting using 2 wrenches.
  9. Tighten the drain clamp on the drain tubing.
  10. Plug the power cord into the wall outlet.
  11. Turn on the water.
  12. Fill the machine with water.
  13. Check for leaks and correct if necessary.