



KIT PART NUMBER 6400080

INSTRUCTIONS FOR DELIMING THE HOT WATER TANK

CHECK THE PARTS RECEIVED IN THE KIT WITH THE PARTS LIST IN THESE INSTRUCTIONS. IF ANY PARTS ARE MISSING, CONTACT THE NATIONAL VENDORS PARTS DEPARTMENT IMMEDIATELY.

Read these instructions carefully before installing the kit.
Keep these instructions for part numbers and for future reference.

This kit contains the following:

INDEX	PART NUMBER	DESCRIPTION	QUANTITY
-	6408156	EVERPURE - SCALEKLEEN - 2.2 LB PKG	1
-	6400136	INSTRUCTIONS	1

1. Use the following table to determine the quantity of ScaleKleen required for your application:

Machine Model	Hot Water Tank Capacity	ScaleKleen Quantity*
Cafe' System 7	2.2 gal	1.1 lb (½ of a 2.2 lb package)
Hot Drink Center/Euro Coffee	5.0 gal	2.2 lb

* This quantity is for the initial de-scaling and will vary with the amount of scale. Use less ScaleKleen for ongoing maintenance and for better water conditions.

2. Determine the method to introduce the ScaleKleen into the hot water tank:
 - If your machine is equipped with an Everpure filter system option and you have the Everpure JT Flushing Can (National Vendors part number 6408157), complete part **A**.
 - If your machine is not equipped with an Everpure filter system option or you do not have the Everpure JT Flushing Can (National Vendors part number 6408157), complete part **B**.

PART A - When you are using the Everpure Flushing Can

1. Close the water shutoff valve at the inlet water valve and Everpure filter head assembly.
2. Pour the proper amount of ScaleKleen into the Everpure JT Flushing Can. Remove the existing filter cartridge and insert the JT Flushing Can into the filter head. Open the water shutoff valve. Vend several cups of water to draw the ScaleKleen into the hot water tank.



-
3. Wait 30 to 40 minutes and then rinse the tank thoroughly following the procedure listed below:
 - Close the water shutoff valve.
 - Remove the JT Flushing Can and reinstall the filter cartridge or replace it with a new filter cartridge based on your maintenance schedule.
 - Drain the hot water tank and discard the water and ScaleKleen solution into the local sewer system.
 - Open the water shutoff valve and fill the tank. Close the water shutoff valve and flush the system by draining the tank.
 - Open the water shutoff valve and fill the tank. Thoroughly rinse the valve and tubing system by vending all selections several times.
 4. Thoroughly rinse the JT Flushing Can with cold water.
 5. Return the machine to service. This completes the deliming procedures.

PART B - When you are not using the Everpure Flushing Can

1. Disconnect power to the machine.
2. Close the water shutoff valve.
3. Remove the required hardware to obtain clear access to the hot water tank.
4. Remove the lid assembly from the tank.
5. Slowly pour the ScaleKleen into the tank. Stir to dissolve.
6. Wait 30 to 40 minutes and verify that the scale is gone.
7. Reinstall the lid assembly onto the tank and any hardware that was removed in step 10 above.
8. Rinse the tank thoroughly by following the instructions below:
 - Drain the hot water tank and discard the water and ScaleKleen solution into the local sewer system.
 - Open the water shutoff valve, connect power to the machine, and fill the tank. Close the water shutoff valve, and flush the system by draining the tank and disposing of the water.
 - Open the water shutoff valve and fill the tank. Thoroughly rinse the valve and tubing system by vending all selections several times.
9. Return the machine to service. This completes the deliming procedures.