

# SERVICE INFORMATION

## M158.0

**MODELS AFFECTED:** All Crane Voce Coffee Machines.

**MODEL NUMBERS:** VOCE 603,605,607

**Revised:** 1/3/2019

**RE:** Reconfigure the Atlas board from UK to US Configuration

**TO SET UP VOCE AS A USA CONFIGURATION:**

1. Open the door of the machine and after about a 5 second delay, a screen will be displayed asking for the entry of a PIN code. The default code for a service technician is four one's.
  - A. The buttons on each side of the screen are assigned as numeric buttons to be used for the entry of the PIN code.
  - B. The buttons below the screen are assigned as an OK button used to accept the entered code, and a reset button to start over if a mistake is made.
2. Press the button labeled 1 four times to enter the default code. A pound sign will be displayed for each digit entered.
3. Press the button labeled OK to accept the entered code once it has been correctly entered the screen will come up displaying the main service menu.
4. Press the button labeled *System Setting*, on the main menu.
5. Press the button labeled *NEXT PAGE*.
6. Press the button labeled *CUSTOM CONFIGURATION*.
7. Press either button labeled *US* or *US\_9oz*.
  - A. **US CONFIGURATION** – Selection **US** will configure the machine as a 12oz vend.
  - B. **US\_9OZ CONFIGURATION** – Selection **US\_9OZ** will configure the machine for a 9oz vend.
8. After selecting the configuration, press *CONTINUE*, the machine will reboot and update the Atlas board to a US cup configurations.